

Pergo Vinyl Transit Underlay**Description:**

- Maximum reduction of Impact Sound
- Maximum reduction of Transition Sound
- Suitable for installation under Flex Click and Rigid Click floors.
- Easy installation
- Can be combined with floor heating/cooling.

**Characteristics:**

Product code	PGVUDLTRANSIT15	
Material	70% recycled Polyester	
Colour	Top layer: Green (may vary) Bottom layer: White	
Shape	Roll	
Thickness	1,2 mm	EN 823
Length	15,31 m	EN 822
Width	0,98 m	EN 822
Compression strength	400 kPa with 3 kPa Pre-load	EN 826
Fire protection classification	E _{fl}	EN 13501 – 1
Thermal conduction resistance	0.045 m ² K/W	DIN 4108
Impact sound insulation	ΔL _w = 21dB with Flex and Rigid Click	IHD 431
Walking noise reduction	-20%	

Installation instructions:

1. Unroll the underlay on the subfloor with the Pergo logo upwards. Lay the underlay strips parallel to the laying direction of your Pergo® floor. Do this strip by strip, as the laying of your floor progresses.
3. Install the following row next to the first. Seal the joints between the underlay with a tape in order to keep the underlay in place.
4. Make sure the underlay fits together tightly (don't leave any gaps).