

# TECHNICAL DATA SHEET

## Pergo Bornholm

Edition 10.2017



### General data

Panel	1820 x 145 mm
Total thickness	14 mm
Numbers of panels per pack	6
m <sup>2</sup> per pack	1,58 m <sup>2</sup>

### Panel build up

Toplayer	PEFC controlled sources	3,2 mm
Core board		Spruce
Backing layer	PEFC controlled sources	Spruce
Tongue and groove	Length	Uniclic
	Width	Perfect Fold 3.0 Connection

### Surface layer

Wood species	Oak/Walnut
Origine	Europe/USA
Finishing	Extra Matt lacquer

### Installation

Floating	On Pergo underlay	CF installation instructions
Glued to subfloor	Pergo MS polymere resin	CF installation instructions

### Warranty

Domestic use	Conditions in each pack	33 years
Uniclic connection		Lifetime
Commercial		On request

### Finishing

UV curing varnish		5 - 7 layers	
Wear resistance	SIS 923509	Falling sand	800 - 1000
	DIN 68861	S 33	100 - 1050
Scratch resistance		Anti-scratch top coat	
Stain resistance	EN 13442	All except blue ink	class 5
		Blue ink	class 3
CE	EN 14342: 2013		DOP PCO 0501
Castor chairs		Use soft castors, type W (EN 12529) and/or suitable office mat	
Slip resistance	CEN/TS 15676		USRV 50-52
Emission of formaldehyde	JIS A5108		F4 Star
PCP			below detection limit
Heat resistance	EN 12664		0,14 m <sup>2</sup> .K/W
Underfloor heating	Suitable	CF special installation instructions	
Reaction to fire	EN 14342	CWFT	Dfl-s1

### Ecological certificates

U-zeichen	Z.156.606-898
AFFSET	A
Nordic ecolabel	3029-0001
PEFC	PEFC/07-32-37
M1	OK
EPD	On request

